PFL Anti-slip Safety Data Sheet



1. Identification of Substance & Company

Product Name PFL Anti-slip
Company Name Peter Fell Limited

Address 81 Patiki Rd, Avondale, Auckland, New Zealand

Telephone Number +64 9 828 6460

Product Use Provide texture and grip to concrete surfaces

2. Hazard Identification

Hazard Classification Non-Hazardous Substance

Non-Hazardous Goods

3. Composition/Information on Ingredients

Chemical Characterisation

Ingredients

Polyethylene Powder, containing pigments and additives

Polyethylene + Additives 96-100% Pigment Masterbatch 0-4%

4. First Aid

Inhalation Remove to fresh air. Seek medical advice if symptoms persist.

Ingestion Rinse mouth with water. Give plenty of water to drink. Do not induce vomiting. Seek

medical advice if symptoms persist.

Skin contact If irritation occurs, wash contact area with soap and water. Molten material will adhere

to skin and cause burns. Cool material as quickly as possible with water. Do not remove material or clothing from skin as this may result in further damage to the skin - see a

physician for removal of the material and treatment of the burn.

Eye If powder gets in the eyes, wash with copious amounts of water, holding eyelids open.

Treat as skin burn if in contact with molten material. In all cases of eye contamination it

is a sensible precaution to seek medical advice.

First Aid Facilities Eye wash and normal washroom facilities

Advice to Doctor Treat symptomatically. Advice as per above information

Firefighting Measures

Extinguishing Media Carbon dioxide, foam, dry chemical, water fog or fine water spray

Special Fire Fighting Procedures Fire fighters must use self-contained breathing apparatus

Unusual Fire and Explosion Hazards High concentration of airborne powders, fines or dust may form explosive mixtures with

air. Risk of dust explosion is increased if flammable vapours are also present.

May accumulate hazardous static charge when agitated in transfer handling systems

Hazchem Code n.a.

Decomposition Temp. > 250°C

6. Accidental Release Measures

Spills and Disposal Dampen down to prevent spread by wind. Shovel or sweep up spilled material and

dispose of or recycle. Disposal of recovered material should conform to local regulations. If large quantities of this material enter the waterways, contact the Environment Protection

Authority or your local Waste Management Authority.

PFL Anti-slip Safety Data Sheet



Storage & Handling

Handling Ensure good ventilation/exhaust at workplace. Avoid contact with eyes and skin. Avoid

> inhalation of dust. Minimise production of fines/dust when handling the polymer. Prevent build up and concentration of fines/dust around handling equipment and on surfaces such

as ducting, structure beams and ceilings.

Earth (ground) all material handling and transfer equipment to dissipate static electricity.

Keep away from uncontrolled heat and other ignition sources.

Storage Store in a cool, dry area

Exposure Controls/Personal Protective Equipment

Engineering Controls Good general ventilation is required under ordinary conditions of use.

Avoid inhaling dusts and fumes generated during use. Use with local exhaust ventilation

during processing.

Personal Protective Equipment Thermal resistant gloves should be worn when handling hot materials.

Use safety glasses. Under dusty conditions, approved respirators to AS/NZ1715 and

AS/NZ1716 should be worn to avoid exposure by inhalation.

Other Exposure Information A limit of 10mg/m3 for nuisance dusts is recommended.

Physical & Chemical Properties

Solid Form **Appearance** Natural Decomposition Temp. > 250°C **Melting Point** 100-140°C **Boiling Point** n.a. Vapour Pressure n.a. Flash Point n.a.

Flammability Combustible solid. May form flammable dust clouds in air. Polymer may burn in presence of

extreme heat and oxygen. Avoid extreme heat.

Auto Ignition Temp. Approx. 350°C

Lower Flammability Limit n.a.

Density (range) 0.930-0.945 Other Information

Water solubility: negligible

10. Stability & Reactivity

Stability Thermal, light, etc.: stable

Conditions to avoid Extreme heat

Incompatibility Strong oxidising agents

Hazardous decomposition products Carbon monoxide, aldehydes, acetic acid, ketones, acrolein, ethane, methane

11. Toxicological Information

Toxicology Information Not Available

Inhalation Inhalation of dust may cause irritation of nose and throat. Fumes given off during

processing can cause respiratory irritation, headache and nausea.

Ingestion No known effects/minimal toxicity. May cause choking if swallowed.Large amounts may

cause nausea and vomiting.

Skin Prolonged skin contact may result in irritational rash. Molten product may cause burns Eyes Molten product may cause burns. Fines and powder may scratch eye surfaces and cause

mechanical irritation. Fumes given off during processing may cause eye irritation.

Chronic Effects None known.

SDS Date:

PFL Anti-slip Safety Data Sheet



12. Ecological Data

Environmental Protection Nodata available

Spilled or waste material must be disposed of in accordance with the applicable local Disposal

Government regulations.

14. Transport Information

U.N. Number n.a. Proper Shipping Name n.a. **DG Class** n.a. Hazchem Code n.a. Packing Group n.a.

Storage and Transport Keep containers closed and check regularly for spills. The products listed in this SDS are not

classified as dangerous goods for any form of transportation or storage.

15. Regulatory Information

Poisons Schedule Not scheduled

Packaging and Labelling No special requirements

Other Information

Manufacturers Advice Conveying lines and equipment in material handling systems should be grounded to

eliminate or reduce the build up of static electricity. Avoid sources of ignition where fines

may occur.

Other Information Since the specific conditions of use of this product are outside the control of the

> supplier, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet is correct to the best of our knowledge and information at the date of publication. The information relates only to the specific product(s) designated and may not be valid for the product if used in

 $combination \ with other products \ or any \ processes \ other than those \ specified \ in the \ text.$

Revision 19/10/2012

End of SDS

SDS Date: Sept 2022