

# Tinted Glaze Sealer

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY

### Product Identifier:

|                               |                                                                                                                                                                                              |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product name                  | Tinted Glaze Sealer                                                                                                                                                                          |
| Synonyms                      | TNTGLZ                                                                                                                                                                                       |
| Proper shipping name          | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound). |
| Other means of identification | n/a                                                                                                                                                                                          |

### Relevant identified uses of the substance/mixture:

|                         |                           |
|-------------------------|---------------------------|
| Relevant identified use | Coloured concrete sealer. |
|-------------------------|---------------------------|

### Details of manufacturer/supplier:

|              |                                                    |
|--------------|----------------------------------------------------|
| Company name | Peter Fell Ltd                                     |
| Address      | 81 Patiki Rd, Avondale, Auckland 1026, New Zealand |
| Telephone    | +64 9 828 6460                                     |
| Website      | www.peterfell.co.nz                                |
| e-mail       | info@peterfell.co.nz                               |

### Emergency telephone number:

|                          |                        |
|--------------------------|------------------------|
| Association/Organisation | National Poison Centre |
| Telephone                | 0800 764 766           |
| Website                  | www.poisons.co.nz      |

## SECTION 2: HAZARD IDENTIFICATION

### Classification of the substance/mixture:

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Classified as Dangerous Goods for transport purposes.

|                     |                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GHS Classification  | Acute Toxicity (Oral) Category 4, Acute Toxicity (Inhalation) Category 5, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Reproductive Toxicity Category 2, Specific Target Organ Toxicity – Repeated Exposure Category 2, Chronic Aquatic Hazard Category 4, Acute Vertebrate Hazard Category 3, Flammable Liquids Category 3, Acute toxicity (Dermal) Category 4. |
| HSNO Classification | 3.1C, 6.1D (dermal), 6.1D (Oral), 6.1E (Inhalation), 6.3A, 6.4A, 6.8B, 6.9B, 9.1D, 9.3C.                                                                                                                                                                                                                                                                                              |

## Label Elements:

Hazard pictogram(s)



Signal Word

Danger

## Hazard statement(s):

|      |                                                                    |
|------|--------------------------------------------------------------------|
| H302 | Harmful if swallowed                                               |
| H333 | May be harmful if inhaled.                                         |
| H315 | Causes skin irritation.                                            |
| H319 | Causes serious eye irritation                                      |
| H361 | Suspected of damaging fertility or the unborn child                |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H413 | Harmful to aquatic life with long-lasting effects.                 |
| H433 | Hazardous to terrestrial vertebrates.                              |
| H226 | Flammable liquid and vapour.                                       |
| H312 | Harmful in contact with skin.                                      |

## Precautionary Statement(s) Prevention:

|      |                                                                                                 |
|------|-------------------------------------------------------------------------------------------------|
| P201 | Obtain special instructions before use.                                                         |
| P210 | Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. |
| P233 | Keep container tightly closed.                                                                  |
| P260 | Do not breath mist/vapour/spray                                                                 |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection.                |
| P240 | Ground and bond container and receiving equipment.                                              |
| P241 | Use explosion-proof electrical/ventilation/lightning/intrinsically safe equipment.              |
| P242 | Use non-sparking tool.                                                                          |
| P243 | Take action to prevent static discharge.                                                        |
| P273 | Avoid release to the environment.                                                               |
| P264 | Wash all exposed external body areas thoroughly after handling.                                 |

## Precautionary Statement(s) Responses:

|                 |                                                                                                                                      |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------|
| P301+P310       | IF SWALLOWED: Immediately call a POISON CENTRE/doctor/physician/first aider.                                                         |
| P308+P313       | IF exposed or concerned: Get medical advice/attention.                                                                               |
| P370+P378       | In case of fire: Use alcohol resistant foam and normal protein foam to extinguish.                                                   |
| P305+P351+PP338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses., if present and easy to do so. Continue rinsing. |
| P304+P312       | IF INHALED: Call a POISON CENTRE/doctor/physician/first aider if you feel unwell.                                                    |
| P314            | Get medical advice/attention.                                                                                                        |
| P337+P313       | If eye irritation persists: Get medical advice/attention.                                                                            |
| P302+P352       | IF ON SKIN: Wash with plenty of water and soap.                                                                                      |
| P303+P361+P353  | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower).                             |
| P332+P313       | If skin irritation occurs: Get medical advice/attention.                                                                             |
| P362+P364       | Take contaminated clothing and wash it before reuse.                                                                                 |

Precautionary Statement(s) Storage:

|           |                                              |
|-----------|----------------------------------------------|
| P403+P235 | Store in a well-ventilated space. Keep cool. |
| P405      | Store locked up.                             |

Precautionary Statement(s) Disposal:

|      |                                                                                                                                  |
|------|----------------------------------------------------------------------------------------------------------------------------------|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|----------------------------------------------------------------------------------------------------------------------------------|

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

| Name          | CAS Number | Proportion |
|---------------|------------|------------|
| Xylene        | 1330-20-7  | 60 - 90%   |
| Acrylic Resin | n/a        | 10 - 30%   |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4: FIRST AID

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

Description of first aid measures:

|              |                                                                                                                                                                           |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye Contact  | - Wash out immediately with fresh running water.                                                                                                                          |
|              | - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.               |
|              | - Seek medical attention without delay; if pain persists or recurs seek medical attention.                                                                                |
|              | - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.                                                                           |
| Skin Contact | - Immediately remove all contaminated clothing, including footwear.                                                                                                       |
|              | - Flush skin and hair with running water (and soap if available).                                                                                                         |
|              | - Seek medical attention in event of irritation.                                                                                                                          |
| Inhalation   | - If fumes or combustion products are inhaled remove from contaminated area.                                                                                              |
|              | - Lay patient down. Keep warm and rested.                                                                                                                                 |
|              | - Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.                                    |
|              | - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. |
|              | - Transport to hospital, or doctor, without delay.                                                                                                                        |
| Ingestion    | - If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.                       |
|              | - If swallowed do NOT induce vomiting                                                                                                                                     |
|              | - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.                        |
|              | - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.                                                       |

## Ingestion (continued)

- Observe the patient carefully.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.
- Avoid giving milk or oils
- Avoid giving alcohol.

## Biological Exposure Index (BEI):

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

| <i>Determinant</i>             | <i>Index</i>       | <i>Sampling Time</i>  | <i>Comments</i> |
|--------------------------------|--------------------|-----------------------|-----------------|
| Methyl hippuric acids in urine | 1.5 gm/gm creatine | End of shift          | Not Available   |
|                                | 2.0 gm/min         | Last 4 hours of shift | Not Available   |

## SECTION 5: FIREFIGHTING MEASURES

## Extinguishing Media

- Foam, Dry chemical powder, BCF (where regulations permit), Carbon dioxide.

## Special hazards arising from the substance or mixture

## Fire Incompatibility

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

## Advice for firefighters

## Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course

## Fire/Explosion Hazard

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.
- Combustible products include: Carbon monoxide (CO) and carbon dioxide (CO<sub>2</sub>)

## SECTION 6: ACCIDENTAL RELEASE MEASURES

## Methods and material for containment and clean up.

## Minor Spills

- Remove ignition sources.
- Clean up spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

## Major Spills

- Clear the area of personnel and move upwind.
- Alert Fire Brigade and tell them the location and nature of the hazard.
- May be violently or explosively reactive.
- Control personal contact with the substance by using protective equipment.

7. STORAGE AND HANDLING

Precautions for safe handling.

|                   |                                                                                            |
|-------------------|--------------------------------------------------------------------------------------------|
| Safe handling     | Containers, even those that have been emptied, may contain explosive vapours.              |
|                   | Do NOT cut, drill, grind, weld or perform similar operations on or near containers.        |
|                   | <b>DO NOT</b> allow clothing wet with material to stay in contact with skin                |
|                   | Electrostatic discharge may be generated during pumping - this may result in fire          |
|                   | Ensure electrical continuity by bonding and grounding (earthing) all equipment.            |
| Other information | Store in original containers in approved flammable liquid storage area.                    |
|                   | Store away from incompatible materials in a cool, dry, well-ventilated area.               |
|                   | <b>DO NOT</b> store in pits, depressions, basements or areas where vapours may be trapped. |
|                   | No smoking, naked lights, heat or ignition sources                                         |

Conditions for safe storage, including any incompatibilities

|                                       |                                                                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Suitable container                    | - Packing as supplied by manufacturer.                                                                                                  |
|                                       | - Plastic containers may only be used if approved for flammable liquid.                                                                 |
|                                       | - Check that containers are clearly labelled and free from leaks.                                                                       |
|                                       | - For low viscosity materials - drums and jerry cans must be of the non-removable head type.                                            |
| Storage incompatibilities<br>(Xylene) | - may ignite or explode in contact with strong oxidisers.                                                                               |
|                                       | - attack some plastics, rubber and coatings                                                                                             |
|                                       | - may generate electrostatic charges on flow or agitation due to low conductivity                                                       |
|                                       | - Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents |
|                                       | - Aromatics can react exothermically with bases and with diazo compounds.                                                               |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits (OEL)

Ingredient Data:

| Source                                         | Ingredient | Material Name              | TWA              | STEL | Peak | Notes |
|------------------------------------------------|------------|----------------------------|------------------|------|------|-------|
| New Zealand Workplace Exposure Standards (WES) | Xylene     | Xylene (o-, m-, p-isomers) | 217 mg/m³/50 ppm | n/a  | n/a  | n/a   |

Emergency Limits:

| Ingredient | Material Names | TEEL 1 | TEEL 2 | TEEL 3 |
|------------|----------------|--------|--------|--------|
| Xylene     | Xylenes        | n/a    | n/a    | n/a    |

| Ingredient    | Original IDLH | Revised IDLH |
|---------------|---------------|--------------|
| Xylene        | 1,000 ppm     | 900 ppm      |
| Acrylic Resin | n/a           | n/a          |

## Exposure Controls

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Appropriate engineering controls | - CARE: Use of a quantity of this material in confined space or poorly ventilated area, where rapid build-up of concentrated atmosphere may occur, could require increased ventilation and/or protective gear.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                                  | - Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: <ul style="list-style-type: none"> <li>- Process controls which involve changing the way a job activity or process is done to reduce the risk.</li> <li>- Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</li> </ul> |
| Personal Protection              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Eye and Face Protection          | - Safety glasses with side shields.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|                                  | - Chemical goggles.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|                                  | - Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Skin Protection                  | - See Hand protection below                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Hand/feet Protection             | - Wear chemical protective gloves e.g. PE/EVAL/PE or PVA or Teflon or Viton.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|                                  | - Wear safety footwear or safety gumboots e.g rubber                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|                                  | - The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application                                                                                                                                                                                                                                                                                                                                                             |
|                                  | - The exact breakthrough time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Body Protection                  | - Overalls                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|                                  | - PVC Apron, PVC protective suit may be required if exposure is severe                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Thermal Hazards                  | - Not Available                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Other Protection                 | Respirator – not normally required, but if used, should have a Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                           |                         |                                      |               |
|---------------------------|-------------------------|--------------------------------------|---------------|
| Appearance                | Coloured viscous liquid | Relative Density to water (water =1) | 0.91          |
| Physical State            | Liquid                  | Auto-Ignition Temperature (°C)       | Not Available |
| Odour                     | solvent                 | Decomposition Temperature (°C)       | Not Available |
| pH                        | Not Available           | Viscosity (cSt)                      | Not Available |
| Melting Point (°C)        | Not Available           | Molecular weight (g/mol)             | Not Available |
| Freezing Point (°C)       | Not Available           | Taste                                | Not Available |
| Boiling Point (°C)        | Not Available           | Explosive Properties                 | Not Available |
| Flash Point (°C)          | 25                      | Oxidising Properties                 | Not Available |
| Evaporation Rate          | Not Available           | Volatile Component (%)               | 80            |
| Explosive Properties      | Not Available           | VOC g/L                              | 825           |
| Upper Explosive Limit (%) | 7.7                     | Solubility in water (g/L)            | Immiscible    |
| Lower Explosive Limit (%) | 0.5                     | Vapour Density in Air (Air = 1)      | 3.66          |

## 10. STABILITY AND REACTIVITY

|                                    |                                                       |
|------------------------------------|-------------------------------------------------------|
| Reactivity                         | - See Section 7.                                      |
| Chemical Stability                 | - Unstable in the presence of incompatible materials. |
|                                    | - Product is considered stable                        |
|                                    | - Hazardous polymerization will not occur.            |
| Possibility of Hazardous Reactions | - See Section 7.                                      |
| Conditions to Avoid                | - See Section 7.                                      |
| Incompatible Materials             | - See Section 7.                                      |
| Hazardous Decomposition Products   | - See Section 5.                                      |

## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects

|                 |                                                                                                                                                                                                                                                                                                                                      |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inhaled         | - The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.                                                                                                                                                                                               |
|                 | - Inhalation hazard is increased at higher temperatures.                                                                                                                                                                                                                                                                             |
|                 | - Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and co-ordination.                                                                                                                           |
| Ingestion       | - The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum. |
|                 | - Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)                                                                                                                                                                                   |
| Skin Contact    | - Skin contact may be harmful; systemic effects may result following absorption.                                                                                                                                                                                                                                                     |
|                 | - The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time.                                                                                                                                                                                                            |
|                 | - Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.                                                                                                                                                                                                                         |
|                 | - Open cuts, abraded or irritated skin should not be exposed to this material                                                                                                                                                                                                                                                        |
|                 | - Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects                                                                                                                                                                                                    |
| Eye             | - There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation.                                                                                                                                                                                             |
| Eye (continued) | - Severe inflammation may be expected with pain.                                                                                                                                                                                                                                                                                     |
|                 | - The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis                                                                                                                                                                                                                        |
|                 | - Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated.                                                                                                                                                                                                                  |
| Chronic         | - Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.                                                                                                                                                                                      |
|                 | - Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.                                                                                                                                                                                             |
|                 | - There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment..                                                                                                                                                                                                  |
|                 | - Women exposed to xylene in the first 3 months of pregnancy showed a slightly increased risk of miscarriage and birth defects.                                                                                                                                                                                                      |

| Material            | Toxicity                                          | Irritation                    |
|---------------------|---------------------------------------------------|-------------------------------|
| Tinted Glaze Sealer | Not Available                                     | Not Available                 |
| Xylene              | Dermal (rabbit) LD50: >1700 mg/kg <sup>[2]</sup>  | Eye (human): 200 ppm irritant |
|                     | Inhalation (rat) LC50: 5000 ppm/4h <sup>[2]</sup> | Eye (human): 200 ppm irritant |
|                     | Oral (rat) LD50: 4300 mg/kg <sup>[2]</sup>        | Eye (rabbit): 87 mg mild      |

Legend: v Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's msds. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|                     |                                                                                                                                                                                                                                                                                           |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tinted Glaze Sealer | - Asthma-like symptoms may continue for months or even years after exposure to the material ceases.                                                                                                                                                                                       |
|                     | - This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.                                                                                                    |
|                     | - Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant                                          |
|                     | - A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. |
| Xylene              | - The material may produce severe irritation to the eye causing pronounced inflammation.                                                                                                                                                                                                  |
|                     | - Repeated or prolonged exposure to irritants may produce conjunctivitis.                                                                                                                                                                                                                 |
|                     | - The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.                                                                                          |
|                     | - The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Reproductive effector in rats                                                                                                                                                     |

## 12. ECOLOGICAL INFORMATION

### Toxicity

|                     |                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tinted Glaze Sealer | - Harmful to aquatic organisms.                                                                                                                                                                                                                                                                                                                                    |
| Xylene              | - log Koc : 2.05-3.08; Koc : 25.4-204; Half-life (hr) air : 0.24-42; Half-life (hr) H2O surface water : 24-672; Half-life (hr) H2O ground : 336-8640; Half-life (hr) soil : 52-672; Henry's Pa m <sup>3</sup> /mol : 637-879; Henry's atm m <sup>3</sup> /mol - 7.68E-03; BOD 5 if unstated - 1.4,1%; COD - 2.56,13% ThOD - 3.125 : BCF : 23; log BCF : 1.17-2.41. |
|                     | - Environmental Fate: Most xylenes released to the environment will occur in the atmosphere and volatilization is the dominant environmental fate process.                                                                                                                                                                                                         |
|                     | - Soil - Xylenes are expected to have moderate mobility in soil evaporating rapidly from soil surfaces                                                                                                                                                                                                                                                             |

### 13. DISPOSAL CONSIDERATIONS

|                               |                                                                                                                                                                                                                                           |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product/Packaging<br>Disposal | - Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Notice 2017.                                                                                                                     |
|                               | - Containers may still present a chemical hazard/ danger when empty                                                                                                                                                                       |
|                               | - Return to supplier for reuse/ recycling if possible.                                                                                                                                                                                    |
|                               | - If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorized landfill. |
|                               | - Where possible retain label warnings and MSDS and observe all notices pertaining to the product                                                                                                                                         |

### 14. TRANSPORT INFORMATION

#### Label Requirements

|                    |                                                                                   |
|--------------------|-----------------------------------------------------------------------------------|
| Label Requirements |  |
| Marine Pollutant   | No                                                                                |
| HAZCHEM            | 3Y                                                                                |

#### Land Transport (UN)

|                               |                                                                                                                                                                                            |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UN Number                     | 1263                                                                                                                                                                                       |
| Packing Group                 | III                                                                                                                                                                                        |
| UN Proper Shipping Name       | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Environmental Hazard          | No relevant date                                                                                                                                                                           |
| Transport Hazard Class(es)    | Class: 3<br>Sub risk: Not Applicable                                                                                                                                                       |
| Special Precautions for users | 163;223;367<br>Limited quantity: 5 L                                                                                                                                                       |

#### Air Transport (ICAO-IATA/DGR)

|                            |                                                                                                                                                                                            |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UN Number                  | 1263                                                                                                                                                                                       |
| Packing Group              | III                                                                                                                                                                                        |
| UN Proper Shipping Name    | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Environmental Hazard       | No relevant date                                                                                                                                                                           |
| Transport Hazard Class(es) | ICAO/IATA Class: 3<br>ICAO/IATA Sub Risk: Not Applicable<br>ERG Code: 3L                                                                                                                   |
| Transport Hazard Class(es) | Special Provisions: A3 A72 A192                                                                                                                                                            |
|                            | Cargo only Parking Instrucitos:306                                                                                                                                                         |
|                            | Cargo Only Maximum Qty/Pack: 220 L                                                                                                                                                         |
|                            | Passenger and Cargo Packing Instructions: 355                                                                                                                                              |
|                            | Passenger and Cargo Maximum Quantity Packing Instructions: 60 L                                                                                                                            |
|                            | Passenger and Cargo Limited Quantity Packing Instructions: Y344                                                                                                                            |
|                            | Passenger and Cargo Limited Quantity Packing: 10 L                                                                                                                                         |

Sea Transport (IMDG-Code/GGVSee)

|                               |                                                                                                                                                                                            |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UN Number                     | 1263                                                                                                                                                                                       |
| Packing Group                 | III                                                                                                                                                                                        |
| UN Proper Shipping Name       | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Environmental Hazard          | No relevant date                                                                                                                                                                           |
| Transport Hazard Class(es)    | IMDG Class: 3                                                                                                                                                                              |
|                               | IMDG Sub risk: Not Applicable                                                                                                                                                              |
| Special Precautions for users | EMS Number: F-E, S-E                                                                                                                                                                       |
|                               | Special Provisions: 163;223;367                                                                                                                                                            |
|                               | Limited quantity: 5 L                                                                                                                                                                      |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

|                                                                                 |            |                    |
|---------------------------------------------------------------------------------|------------|--------------------|
| Source                                                                          | Ingredient | Pollution Category |
| IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk | Xylene     | Y                  |

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

This substance can be managed under the controls specified in the Transfer Notice or alternatively, it may be managed using the conditions specified in an applicable Group Standard.

|            |                |
|------------|----------------|
| HSR Number | Group Standard |
| HSR007211  | Not Available  |

Regulatory Lists

- Xylene (1330-20-7) is found on the following regulatory lists:
- Internation Agency for Research on Cancer (IARC); Agent Classified by the IARC Monographs
  - New Zealand Hazardous Substances and New Organisms (HSNO) Act – Classification of Chemicals.
  - New Zealand Inventory of Chemicals
  - New Zealand Workplace Exposure Standards (WES)

Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present.

|              |                                                             |                                                                                |
|--------------|-------------------------------------------------------------|--------------------------------------------------------------------------------|
| Hazard Class | Quantity beyond which controls apply for closed containers. | Quantity beyond which controls apply when use is occurring in open containers. |
| 3.1C         | 500 L in containers greater than 5 L                        | 250 L                                                                          |
|              | 1,500 L in containers up to and including 5L                | 250 L                                                                          |

Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

|                    |                |
|--------------------|----------------|
| Class of Substance | Quantities     |
| Not Applicable     | Not Applicable |

16. OTHER INFORMATION

|             |            |
|-------------|------------|
| SDS Created | April 2025 |
| SDS Updated | April 2025 |

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC—TWA: Permissible Concentration-Time Weighted Average
- PC—STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit.
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL : No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: Bioconcentration Factors
- BEI: Biological Exposure Index
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European Inventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances.